

**Declaration of Performance No.:**

**5801-01-1-2014**

1.	Unique identification code of the product type:  <b>KLEIBERIT 580</b>
2.	Type, batch or serial number of any other element allowing identification of the construction product as required pursuant to Article 11 (4):  <b>Batch description see label on packaging</b>
3.	Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:  <b>Sealant for non-structural use in joints in buildings for facade elements; for exterior and interior applications. EN 15651-1: F EXT-INT (F 12,5P)</b>
4.	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):  <b>KLEIBERIT SE &amp; Co. KG Max-Becker-Straße 4 76356 Weingarten / Baden</b>
5.	Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 (2):  <b>not applicable / not relevant</b>
6.	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:  <b>System 3 plus 3</b>
7.	In case of the declaration of performance concerning a construction product covered by a harmonized standard:  <b>The notified body Ginger CEBTP, identification number 0074, performed the type tests and issued the test report.</b>
8.	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:  <b>not applicable / not relevant</b>
9.	Declared performance: Conditioning: Procedure A; substrate: mortar M2, aluminum without primer

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire (EN 13501)	Class E	EN 15651-1:2012-12
Hazardous substances	Evaluated	
Resistance to flow (EN ISO 7390)	≤ 3 mm	
Loss of volume (EN ISO 10563)	≤ 25 %	
Adhesion / cohesion properties after immersion in water (EN ISO 10591)	≥ 100 %	
Durability (ISO 8339, ISO 9046, ISO 10591)	Passed	

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

**Not applicable**

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.  
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

ppa. Dr. Steffen Wunderlich, Liquid Reactive Adhesives Manager

(name and function)

Weingarten, 15.05.2023

(place and date of issue)

(signature)